

# Technical Data Sheet

## BS-3366 Premium D2 Wood Glue

**Features**

- ◆ Water-resistant D2
- ◆ Indoor use only
- ◆ Easy to spread
- ◆ High bond strength
- ◆ Fast curing
- ◆ Forms thin gapless layer when set
- ◆ Non-toxic, solvent free and low odour

**Available Colours**

- ◆ Light yellow (Wet)
- ◆ Yellowish transparent (Dry)

**Storage**

- ◆ Store in a dry and cool place with temperature below +30°C.

**Shelf life:**

- ◆ 24 months

**Packaging**

- ◆ 125 g / bottle ~ 12/ box; 144/ carton
- ◆ 250 g / bottle ~ 12/ box; 72/ carton
- ◆ 500 g / bottle ~ 24/ carton

### Product Specification

|   |                      |
|---|----------------------|
| Appearance                                  | : Viscous Liquid     |
| Specific Gravity                            | : 1.05 - 1.10        |
| Viscosity at 25 °C (Brookfield LV 3 @ 5rpm) | : 8,000 - 12,000 cPs |
| Solid Content                               | : 38.0 - 40.0%       |
| pH  | : 4.0 - 5.0          |
| Wet Tack                                    | : Aggressive         |
| Flammability                                | : Non Flammable      |

### Description

A D2 grade wood glue formulated for indoor woodworking applications with limited exposure to humidity. It offers quick setting, superior bonding strength, and versatility across various substrates. It is non-toxic, solvent free and easy cleans up with water.

### Applications

Idea for indoor wood joining, furniture repair, wooden frames, and woodworking projects which limited exposure to high humidity. **Note:** Not for continuous submersion or use below the waterline.

### Directions

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Apply the adhesive on both surfaces if the material is porous. Press together firmly and leave to dry.
3. Replace cap after use and store in a cool, dry place.

### Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.